

Turntable Pallet Wrapper

Automatic wrapping cycle with operator loading and manual film handling.



Reference configuration shown. Supply scope is specified in the quotation.

2,000 kg

REFERENCE LOAD

1,650 mm

TURNTABLE DIAMETER

25–40/h

REFERENCE OUTPUT

Why this format

Repeatable wrapping

Adjustable turntable speed and wrap programs support routine pallet loads.

Controlled film delivery

Pre-stretch is specified for the listed reference carriage; confirm the supplied carriage and ratio.

Flexible loading

Turntable, mast, ramp and load-support options are selected for the application.

Operating sequence

01 Position the pallet and attach the film.

02 Select the program and run the automatic wrap cycle.

03 Cut and secure the film tail; remove the wrapped load.

Configure the machine around your product

Send dimensions, weight, material, target output and destination power supply.

[View the product / request a quotation →](#)



Reference specifications

Reference configuration only. Final supply follows the approved quotation and drawings.

Parameter	Reference value / condition
Operating arrangement	Automatic wrap cycle; manual loading and film handling
Turntable diameter	1,650 mm reference
Reference pallet size	Approx. 1,200 × 1,200 mm; confirm diagonal and overhang
Maximum load weight	2,000 kg reference configuration
Wrapping height	500–2,000 mm reference; other heights by quotation
Turntable speed	3–12 rpm, adjustable
Reference output	25–40 pallets/hour; depends on load and cycle settings
Film carriage / pre-stretch	Reference pre-stretch carriage: up to 250%; confirm supply
Reference machine size	2,650 × 1,650 × 2,480 mm (L × W × H)
Reference machine weight	Approx. 500 kg
Installed power	2.3 kW reference configuration
Reference power supply	220 V, single phase
Other destination voltages	110 / 120 / 230 / 380 / 415 V configurations on request

Configuration options

Larger turntables (1,800 / 2,000 / 2,200 mm); extended mast; loading ramp; top platen; weighing; labelling; automatic film handling. Availability and inclusion are confirmed in the quotation.

Information needed for selection

Pallet length, width and diagonal; load height, weight and stability; film specification; target output; loading method; destination electrical supply.

Configuration note

The reference pre-stretch carriage is not a promise that every FY-PWPM01 variant has the same carriage. Automatic wrapping does not imply automatic film attachment or cutting. Reference data is carried forward from Rev A; the operating description follows the existing product-page workflow. Images may show optional equipment. Layout and wording revision: 07 Sep 2026.